

Technical Data Primers & Ancillaries

WEATHERCOAT FILLER

Product Description

WEATHERCOAT FILLER is a ready to use exterior graded filler based on special Nano Emulsion of 100% pure acrylic binder. Can be applied straight to most fair-face surfaces such as concrete, plasterboard walls and ceilings, brick or block work. – for exterior and if required can use for interior also. WEATHERCOAT FILLER can be subsequently overcoated with various Berger Range of Paint finishes.

Recommended Areas of Application

Area of use : Mainly for Exterior, can be also use for Interior
Substrate : Concrete, plaster board walls, ceiling, brick or block work.

Technical Data

Sheen Variants : Matt
Colours : White
Volume Solids : 52 ± 2%

Theoretical Covering Capacity	Dry Film Thickness per coat		Theoretical Spread rate
	Typical	1 - 2 mm	2 – 2.5 Kg/m ²

Practical Covering Capacity : For estimation of practical covering capacity, following factors to be considered: surface profile, uneven application, application losses, losses in container and equipment, etc.

Drying time	Substrate temp.	Touch dry	Overcoating Interval	
			Minimum	Maximum
	25 °c	3 hours	8 hours	Indefinite
	35 °c	2 hours	6 hours	
	45 °c	1 hours	3 hours	

Application Data

Method of application : Putty knife or Trowel

Thinner : Sweet Water

Thinning ratio (by vol.) : N/A

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Note: Fungal growth should be treated with Bison Fungicidal Solution. After drying, one coat of Plastaseal Penetrating Sealer can be applied if required.

Applications Details

Ensure adequate ventilation during application and drying.

- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

Trowel: Used for filling surface irregularities, indentations and undulations to produce a smooth and level surface prior to painting. Because of its excellent hiding power, it can cover blemishes or imperfections on the existing surface. Wherever required, the trowel marks can be removed by lightly applying sandpaper after drying and with subsequent cleaning.

TYPICAL PAINT SYSTEM

1 or 2 coats x Weathercoat Filler

Followed by recommended paint system

*For alternate system suggestion please contact Berger Paints Sales Representative

Storage, Safety Information And Precautions

Keep out of reach of children.

- Store in cool, dry conditions; ensure adequate ventilation during application.
- Shelf life up to 24 months from the date of manufacture.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls,
- goggles, dust masks and gloves.

First-Aid

- Eyes: In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water, or with an approved industrial cleaner.
- Do not use solvents.
- Inhalation: Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion: Do not induce vomiting. Obtain immediate medical attention.
- Refer MSDS for disposal procedures.

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.

This Technical Data Sheet supersedes those previously issued with immediate effect