

SELECT RUSTIC DECOR

Product Description

Berger Rustic Decor is a synthetic render-cum-finish which can be applied straight to most fairface surfaces such as concrete, plaster, brickwork-both exterior and interior. Rustic Decor is a ready mixed coating composed of durable polymer resins incorporating different sized and graded marble granules. With its unique engraved finish, Berger Rustic Decor is truly a decorative plaster and a superb finish-both in one. Rustic Decor incorporates fungicides and algacides which give good microbial resistance. Berger Rustic Decor has Good Ultra Violet (UV) resistance and adhesion on various surfaces. Berger Rustic Decor has a 'Breathable Film' that breathes out trapped moisture both from the paint surface as well as the substrate.

Recommended Areas of Application

Area of Use: Exterior

Technical Data

Sheen Variants: Unique engraved finish, Matt

Colours: White & Limited colours.

Volume Solids: 70 ± 2%

Theoretical Covering Capacity

Depends on the surface profile and coat thickness. For a reasonably fairface : surface, 0.7 – 0.9 m² per litre may be achieved for a coat thickness of upto 1mm.

Practical Covering Capacity

For estimation of practical covering capacity, following factors to be taken into account: surface profile, uneven application, over spray, losses in container and equipment etc.

	Substrate Temp.	Touch Dry	Overcoating Interval	
			Minimum	Maximum
Drying time	35°C	1 hour	4 hours	Indefinite
	35°C	1 hour	4 hours	Indefinite
	35°C	1 hour	4 hours	Indefinite

Application Data

Method of Application : Trowel, Spatula

Thinner : Sweet water

Thinning Ratio (by vol.) : N/A

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Note: Dusting or chalking surface should be consolidated using Plastaseal Penetrating Sealer

Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.
- Apply Rustic Decor by a trowel or a spatula or even a roller to obtain an even coating of around 1 mm thickness.
- Allow to set for 5-15 minutes.
- Rub the face of the applied area with a stainless steel or plastic trowel, which will roll on the coarsest grains in the coating and produce the desired engraved finish.

Note: Depending on the area of use, other systems can be recommended.

TYPICAL PAINT SYSTEM

Interior

1 coat x Berger Alkali Resistant Primer

1coat x Select Rustic Decor

For alternate system suggestion please contact Berger Paints Sales Representative

Storage, Safety Information And Precautions

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Shelf life up to 12 months from the date of manufacture.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.

First-Aid

- Eyes: In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation: Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion: Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the datasheet may be modified by us without notice.

*"This Technical Data Sheet supersedes those previously issued with immediate effect
 For more information please contact us at: customerservice.oman@asianpaints.com"*

Asian Paints (Middle East) LLC
 Ghala Industrial Area, Al - Khuwair
 Postal Code : 133, P.O Box :462
 Sultanate of Oman