

Material Safety Data Sheet

SOLVALUX 7-73

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product Name : Solvalux 7-73
Product Type : Thinner
Supplier : Berger Paints Emirates Limited
P O Box 27524, Dubai, UAE
Telephone Number : 009714-3391000
Emergency Telephone Number : 009714-3391078

2. COMPOSITION/INFORMATION ON INGREDIENTS :

	<u>Weight%</u>	<u>CAS Number</u>	<u>LEL Vol%</u>	<u>ACGIH TLV-TWA</u>
• Aromatic hydrocarbon	<60	1330-20-7	1.2	100 ppm
• Methoxy Propyl Acetate	<60	108-65-6	1.5	Not known

3. HAZARDS IDENTIFICATION :

Human Health Hazards : Harmful by inhalation and in contact with skin. Irritating To skin. Narcotic at high vapour pressure. Aspiration Into the lungs may cause chemical pneumonitis. May Impair fertility. Swallowing may cause headache, nausea, vomiting, breathing difficulties and weakness. Possible kidney damage may result from ingestion of large quantities of material.

4. FIRST AID MEASURES :

General : Remove contaminated clothing.
First Aid - Inhalation : Remove to fresh air. If rapid recovery does not occur, obtain medical attention.
First Aid - Skin : Remove contaminated clothing immediately. Wash skin thoroughly with soap and water.
First Aid - Eye : Irrigate copiously with clean, fresh water for atleast 10 minutes, holding the eye lids apart and seek medical advice.
First Aid - Ingestion : Do not induce vomiting. Obtain immediate medical attention.

5. FIRE FIGHTING MEASURES :

Specific hazards : Fire will produce dense, black smoke. Inhalation of decomposition products may cause serious health hazards.
Extinguishing media : Water spray-mist, foam, dry chemical powder, carbon dioxide, sand.
Unsuitable extinguishing media : Water in a jet.

6. **ACCIDENTAL RELEASE MEASURES :**

Personal precautions	: Avoid contact with skin and eyes. Do not breathe vapour. Extinguish naked flames. Remove ignition sources. Avoid sparks.
Personal protection	: Wear PVC gloves, safety boots. Wear full face-piece respirator with organic vapour canister NPF 400. In a confined space, wear self-contained breathing apparatus open circuit type NPF 2000.
Environmental precautions	: Prevent contamination of soil and water.
Processing for Cleaning/ Collecting	: Contain and collect spillage with non-combustible absorbent materials, e.g., sand, earth or spill control material and place in a container for disposal according to local regulation.

7. **HANDLING AND STORAGE:**

Avoid prolonged or repeated contact with skin. Do not breathe vapour, spray/mists. Extinguish any naked flames. Remove ignition sources. Avoid spark. Do not smoke. Take precautionary measures against static discharges.

Handling temperature	: Ambient
Storage	: Keep container tightly closed and in a well ventilated place. Keep away from direct sunlight and other sources of heat or ignition. Do not smoke in storage areas.
Storage temperature	: Ambient.

8. **EXPOSURE CONTROLS/PERSONAL PROTECTION :**

Engineering Control measures	: Use only in well ventilated areas.
Respiratory protection	: When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: PVC gloves. Barrier creams may help to protect the exposed areas of the skin.
Eye protection	: Use safety eyewear designed to protect against splash of products.

9. **PHYSICAL AND CHEMICAL PROPERTIES :**

Physical state	: Liquid
Odour	: Paraffinic
<u>Safety related information :</u>	<u>Value</u>
Flash Point	25 - 30°C
Ignition temperature	> 350°C
Boiling Point	137°C (Based on Xylene)
Vapour Density (Vs. Air)	Heavier
Evaporation Rate (Vs. n-Bu. Acetate)	Slower
Density at 25°C	0.90 – 0.92 gm/cc
Solubility in water	In-soluble.

10. **STABILITY/REACTIVITY :**
 Stability : Stable under normal use conditions. Polymerised in presence of oxygen.
 Conditions to avoid : Heat, flames and sparks
 Materials to avoid : Strong oxidizing agents and alkalies.
 Hazardous decomposition : Carbon mono-oxide and/or carbon di-oxide.
 Products
11. **TOXICOLOGICAL INFORMATION :**
 Basis for assessment : This product was not tested but the information given is based on the known toxicological data of the constituents.
 Acute toxicity - oral : LD 50 expected to be above 2000 mg/kg based on Xylene
 Acute toxicity - dermal : LD 50 expected to be above 2000 mg/kg based on Xylene
 Acute toxicity - inhalation : LC 50 expected to be > 5 mg/l
 Eye irritation : The liquid splashed in the eyes may cause irritation.
 Skin irritation : Not a skin sensitiser but prolonged contact with the preparation may cause removal of natural fat from the skin resulting to dermatitis.
12. **ECOLOGICAL INFORMATION** : Avoid contamination of earth, rivers, lakes or sewages
 Water contamination class : 2 (self classification)
13. **DISPOSAL CONSIDERATIONS :**
 Precautions : Refer to Section 7
 Waste disposal : Recover or recycle if possible. Otherwise incineration.
 Container disposal : Allow the residue to dry and dispose of as scrap metal.
14. **TRANSPORT INFORMATION :**
 UN Number : 1263
 IMCO Class : 3.3
 Page Number : 3149
 Marine Pollutant : Yes
 Proper shipping name : Thinner
15. **REGULATORY INFORMATION :**
 • EC Classification : Flammable dangerous for the environment
 Contains : Ethoxy Ethanol
 • EC Risk phrases
 R10 : Flammable.
 R20/21 : Harmful by inhalation and in contact with skin.
 R38 : Irritating to skin.
 • EC Safety Phrases
 S13/25/45/53 : Avoid contact with eyes.

16. **DISCLAIMER** :

This information is based on our current knowledge and is obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding the correctness. This information is extended to describe the product for the purposes of health, safety and environmental requirements only. The conditions or methods of handling, storage, use or disposal of the product are beyond our control. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage connected with the handling, storage, use or disposal of the product.